

Volume 25, Numbers 1-3, April 1995

## Contents

Gas Sensors	
Material and design considerations for low-power microheater modules for gas-sensor applications	343
Pore size and pore-size distribution control of porous silica	347
A new type of gas sensor based on the semiconductor-cleft-semiconductor structure	353
Capacitive sensors in CMOS technology with polymer coating	357
Steady-state model of a zirconia oxygen sensor in a simple gas mixture	362
Reception tuning of gas-sensor microsystems by selective coatings:	366
Donor-doped Gd <sub>2</sub> Ti <sub>2</sub> O <sub>7</sub> as a semiconductor-type oxygen sensor	370
Semiconductor dimethylamine gas sensors with high sensitivity and selectivity	375
A tip-type carbon dioxide gas-sensor probe based on lithium and oxide ionic conductors	380
A.c. impedance analysis of gas-sensing property in CuO/ZnO heterocontacts	383
Metal oxide semiconductor NO <sub>2</sub> sensor	388
Capacitive-type sensors for the selective detection of nitrogen oxides	392
Application of metal tungstate-carbonate composite to nitrogen oxides sensor operative at elevated temperature J. Tamaki, T. Fujii, K. Fujimori, N. Miura, N. Yamazoe (Fukuoka, Japan)	396
Physical description of the principle of an SO <sub>2</sub> sensor	400
Combustion gas sensitivity of zeolite layers on thin-film capacitors	403
Development and testing of a solid-state CO <sub>2</sub> gas sensor for use in reduced-pressure environments	407
A capacitive CO <sub>2</sub> sensor with on-chip heating	412
The thick-film route to selective gas sensors	415
A polycrystalline diamond thin-film-based hydrogen sensor	421
A new method using a catalytic sensor for the identification and concentration measurement of combustible gases	426

Vapour and gas sensing by noise measurements on polymeric balanced bridge microstructures	. 42
Highly sensitive and selective H <sub>2</sub> S gas sensor from r.f. sputtered SnO <sub>2</sub> thin film	. 433
Amperometric response of ambient temperature oxygen sensors based on insulating material-dispersed PbSnF <sub>4</sub> layers H. Hanamoto, K. Tsuchiya, J. Kuwano (Tokyo, Japan)	438
Detection of organic solvents with reliable chemical sensors based on cellulose derivatives	. 443
The influence of morphology on the response of iron-oxide gas sensors	448
Gas sensing using a charge-flow transistor	
Transition between neck-controlled and grain-boundary-controlled sensitivity of metal-oxide gas sensors	454
Development of a fiber-optic chemical sensor for multicontaminant monitoring of environmental systems K.M. Leonard (Huntsville, AL, USA)	458
On-line chemical sensors for high-temperature coal gases: the influence of humidity	462
SnO <sub>2</sub> thin films for gas sensor prepared by r.f. reactive sputtering	465
The influence of deposition parameters on the performance of tin dioxide NO2 sensors prepared by radio-frequency	
G. Williams, G.S.V. Coles (Swansea, UK)	469
Surface morphology and gas-sensing characteristics of $SnO_{2-x}$ thin films oxidized from Sn films	474
Tin oxide micro gas sensor for detecting CH <sub>3</sub> SH	478
Characterization of porous tin oxide thin films and their application to microsensor fabrication	482
CO gas sensor based on Au-La <sub>2</sub> O <sub>3</sub> loaded SnO <sub>2</sub> ceramic	486
The effect of humidity on tin-oxide thick-film gas sensors in the presence of reducing and combustible gases D.S. Vlachos, P.D. Skafidas, J.N. Avaritsiotis (Athens, Greece)	491
Simulation of the effect of fractional dimension on tin-oxide-based gas sensors	495
Sensing characteristics of ISFET-based hydrogen sensor using proton-conductive thick film	499
Thin tin-oxide film alcohol-gas sensor	504
The influence of the tin-oxide deposition technique on the sensitivity to CO	507
The interaction of different oxidizing agents on doped tin oxide	512
Temperature dependencies of sensitivity and surface chemical composition of SnO <sub>x</sub> gas sensors	516
Moisture effects on pure and Pd-doped SnO <sub>2</sub> thick films analysed by FTIR spectroscopy and conductance measure-	
G Ghiotti A Chiorino (Turin Italy) G Martinelli M C Carotta (Ferrara Italy)	520

Contents

Comparison between two Figaro sensors (TGS 813 and TGS 842) for the detection of methane, in terms of selectivity	
and long-term stability	525
Ca- and Pt-catalysed thin-film SnO <sub>2</sub> gas sensors for CO and CO <sub>2</sub> detection	529
A cluster approach for the adsorption of oxygen and carbon monoxide on SnO <sub>2</sub> and CdS surfaces	532
Tin oxide (SnOx) carbon monoxide sensor fabricated by thick-film methods	537
An IR study of CO-sensing mechanism on Au/ZnO	540
A selective CH <sub>4</sub> sensor using semiconducting Ga <sub>2</sub> O <sub>3</sub> thin films based on temperature switching of multigas reactions M. Fleischer, H. Meixner (Munich, Germany)	544
Aqueous ozone detector using In <sub>2</sub> O <sub>3</sub> thin-film semiconductor gas sensor	548
Physical interpretation of the influence of humidity on an SO <sub>2</sub> sensor	552
Research and development of gas sensors in China	555
Ultrafine grain-size tin-oxide films for carbon monoxide monitoring in urban environments	559
Chemical and electronic characterization of pure SnO <sub>2</sub> and Cr-doped SnO <sub>2</sub> pellets through their different response to NO	564
G. Ghiotti, A. Chiorino, F. Prinetto (Turin, Italy)	304
Structural and electrical characterization of PVD-deposited SnO <sub>2</sub> films for gas-sensor application	568
A study of tin-dioxide gas-sensor thermochemistry under conditions of varying oxygen partial pressure	
Sensor-array calibration time reduction by dynamic modelling	578
Development of a high-temperature basic device for chemical sensors based on an IDC with on-chip heating C. Scheibe, E. Obermeier (Berlin, Germany), W. Maunz, C. Plog (Friedrichshafen, Germany)	584
A novel method for the preparation of NH <sub>3</sub> sensors based on ZnO-In thin films	588
A study of gas-sensing properties of sputtered $\alpha$ -SnWO <sub>4</sub> thin films	591
Response of lead phthalocyanine to high NO <sub>2</sub> concentration	596
Microstructure and response behaviour of electrodes for CO <sub>2</sub> gas sensors based on solid electrolytes A. Dubbe (Matsuyama, Japan), HD. Wiemhöfer (Tübingen, Germany), Y. Sadaoka (Matsuyama, Japan), W. Göpel (Tübingen, Germany)	600
CH <sub>4</sub> optical sensor using a 1.31 μm DFB laser diode	603
Carbon dioxide sensor using NASICON prepared by the sol-gel method	607
Thick-film zinc-oxide gas sensor for the control of lean air-to-fuel ratio in domestic combustion systems	610
A comparison of conductance behaviour between SnO <sub>2</sub> and CdS gas-sensitive films	614
Selective nitrogen dioxide sensor based on nickel copper oxide mixed with rare earths	619

Zinc-oxide-based semiconductor sensors for detecting acetone and capronaldehyde in the vapour of consommé soup Y. Anno, T. Maekawa, J. Tamaki (Kasuga, Fukuoka, Japan), Y. Asano, K. Hayashi (Tokyo, Japan), N. Miura, N. Yamazoe (Kasuga, Fukuoka, Japan)	623
Influence of chemical composition on sensitivity and signal reproducibility of CdS sensors of oxygen	628
Study of the behaviour of CeO <sub>2</sub> in SO <sub>2</sub> -containing environment	631
CO <sub>2</sub> monitoring by solid-state limiting-current sensors	636
Sensitivity mechanism of metal oxides to oxygen detected by means of kinetic studies at high temperatures J. Gerblinger, U. Lampe, H. Meixner (Munich, Germany)	639
Response of chemically modified PrPc <sub>2</sub> , PrPc <sub>2</sub> and GdPc <sub>2</sub> Langmuir-Blodgett films to tobacco smoke	643
Interaction between collective and local subsystems in semiconductor surface-active structures	647
Impedance of zeolite-based gas sensors	653
Carbon-monoxide sensors based on thin films of BaSnO <sub>3</sub>	657
NO <sub>2</sub> sensitive LaFeO <sub>3</sub> thin films prepared by r.f. sputtering	661
A new method for on-vehicle detection of catalyst malfunction based upon measurement of non-equilibrated gas	
P.G. Eastwood, S. Fischer, M. Schweizer-Berberich (Tübingen, Germany), G. Girardi (Milan, Italy), W. Göpel (Tübingen, Germany)	665
Organometallic polymer membrane for gas detection applied to a surface acoustic wave sensor	670
Niobium-doped α-Fe <sub>2</sub> O <sub>3</sub> semiconductor ceramic sensors for the measurement of nitric oxide gases	673
Humidity Sensors	
A study of low-cost sensors for measuring low relative humidity	681
Sensor calibration of a SAW resonator for absolute humidity measurements in microelectronic packages P.H. Huang (Gaithersburg, MD, USA)	686
Humidity sensor durable at high humidity using simultaneously crosslinked and quaternized poly(chloromethyl	
Y. Sakai, Y. Sadaoka, M. Matsuguchi, H. Sakai (Matsuyama, Japan)	689
A thin-film polysulfone-based capacitive-type relative-humidity sensor	692
A study of condensation and dew point using a SAW sensor	696
High-temperature humidity sensor using a limiting-current-type plane multi-oxygen sensor for direct firing system H. Yagi, K. Ichikawa (Iwasaki Komaki, Aichi, Japan)	701
Sol-gel processed TiO <sub>2</sub> -based thin films as innovative humidity sensors	705
A capacitive-type humidity sensor using crosslinked poly(methyl methacrylate-co-(2 hydroxypropyl)-methacrylate) C. Roman, O. Bodea, N. Prodan, A. Levi, E. Cordos (Cluj-Napoca, Romania), I. Manoviciu (Timisoara, Romania)	710
Study of the conduction mechanism of La <sub>2</sub> CuO <sub>4</sub> -ZnO heterocontacts at different relative humidities	714

Ion Sensors	
Disposable ion-selective electrodes	72:
All-solid-state potassium-selective electrode using double-layer film of polypyrrole/polyanion composite and plasticized poly(vinyl chloride) containing valinomycin	
A solid membrane sensor for chromate ions	729
Cu <sup>2+</sup> -selective thin films for chemical microsensors based on sputtered copper-arsenic-selenium glass E.A. Bychkov, M. Bruns, H. Klewe-Nebenius, G. Pfennig, W. Hoffmann, H.J. Ache (Karlsruhe, Germany)	733
Models and methods of determining the transient response of ion sensors: comparison with impedance spectroscopy M. Attari (Saint Martin d'Hères, France and Algiers, Algeria), P. Fabry (Saint Martin d'Hères, France), G. Quezel, H. Mallié (Grenoble, France)	
Application of a proton-conducting electrolyte for a pH sensor	741
Optical Sensors	
Simultaneous determination of refractive index and absorbance spectra of chemical samples using surface plasmon	
S.R. Karlsen, K.S. Johnston, R.C. Jorgenson, S.S. Yee (Seattle, WA, USA)	747
Coulometric measuring system based on carbon felt electrode and glucose oxide	750
Optical viscosity sensor using forward light scattering	753
Near-infrared surface plasmon resonance in silicon-based sensor: new opportunities in sensitive detection of biomolecules from aqueous solutions by applying microstep for discriminating specific and non-specific binding	
Feasibility of evanescent wave interferometer immunosensors for pesticide detection: chemical aspects L.M. Lechuga, A.T.M. Lenferink, R.P.H. Kooyman, J. Greve (Enschede, Netherlands)	762
Sensor Systems	
Sources of systematic errors in chemical sensor chemometrics	769
Highly sensitive odour sensors using various SnO <sub>2</sub> thick films	773
Improvement of surface acoustic wave gas sensor response time using neural-network pattern recognition  D. Rebière, C. Bordieu, J. Pistré (Talence, France)	777
Design of sensor arrays by use of an inverse feature space	781
A systematic investigation on the use of time-dependent sensor signals in signal-processing techniques	
Continuous determination and discrimination of mixed odour vapours by a new chemiluminescence-based sensor	
K. Utsunomiya, M. Nakagawa, N. Sanari, M. Kohata, T. Tomiyama, I. Yamamoto, T. Wada, N. Yamashita, Y. Yamashita (Okayama, Japan)	790
Identification of aromas from wine using quartz-resonator gas sensors in conjuction with neural-network analysis H. Nanto, S. Tsubakino, M. Ikeda, F. Endo (Ishikawa, Japan)	794
Application of semiconductor gas sensor to quality control of meat freshness in food industry	797
Complex chemical pattern recognition with sensor array: the discrimination of vintage years of wine	801
Non-linear signal evaluation with linear regression techniques for redundant signals	805

A composed neural network for the recognition of gas mixtures	
Technology and Materials	
Role and mechanism of the formation of hydrogen-induced interface states for platinum/silicon oxide/silicon MOS	
tunnelling diodes	81
Highly sensitive taste sensor with a new differential LAPS method	81
Photocurable polymers applied as encapsulating materials for ISFET production	82
Double-layer granular SnO <sub>2</sub> sensors	82
Structure identification of non-linear models for QMB polymer-coated sensors	83
Hydrogen-sensing mechanism of zinc oxide varistor gas sensors	84:
Optical CO detection by use of CuO/Au composite films	85
State of sensing technology development in China	854
Application of the air-bridge microheater to gas detection	85
Application of bistable nature of metal surface in aqueous solution to an oxygen sensor	861
Connectivity of pore networks in chemically sensitive materials	865
Semiconductor/metal/gas behaviour through surface-potential change	871
LB-based PAB immunosystem: activity of an immobilized urease monolayer	876
The effect of film oxygen content on $SnO_x$ gas-sensor selectivity	883
Surface composition of alkali-doped TiO <sub>2</sub> films for sensors investigated by XPS	886
Characterization of silicon transducers with Si <sub>3</sub> N <sub>4</sub> sensing surfaces by an AFM and a PAB system	889
Investigation of electrical properties of high-resistivity materials for solid-state sensors	894
Chip-array electrodes for simultaneous stripping analysis of trace metals	899
Application of a new technique for temperature-profile measurements in microheaters	904
Author Index of Volumes B24 and B25	907
Subject Index of Volumes B24 and B25	910

The publisher encourages the submission of articles in electronic form thus saving time and avoiding rekeying errors. A leaflet describing our requirements is available from the publisher upon request.

